

Certificate of Approval

Certificate Number: MCS IK0193

Issue: 03

Wagner Renewables Ltd.

Unit 3, Keynor Farm Sidlesham West Sussex PO20 7LL, UK



Having complied with the requirements of the following

MCS 010-Issue 1.5

Factory Production Control Requirements

MCS 012: Issue 1.2

Product Certification Scheme Requirements: Pitched Roof Installation Kits

is authorised to use the BRE Global Certification Mark and the MCS Certification Mark in association with the following products:

Products

Please see Appendix for details

This contificate and appendix is maintained and held in force through periodic review and verification.

Signed for BRE Global Ltd.

John Holden

02 June 2017

20 June 2014

Business Group Manager

Date of Issue

Date of First Issue





This certificate and appendix remains the property of BRE Global Ltd and is issued subject to terms and conditions (for details visit www.greenbooklive.com/terms).

To check the validity of this certificate please visit www.greenbooklivecom/check or contact us.

BRE Global Ltd., Garston, Watford WD25 9XX.

T: +44 (0)333 321 8811 F: +44 (0)1923 664603 E: enquiries@breglobal.com MCS is the Certification Mark for Onsite Sustainable Energy Technologies





Appendix to Certificate No: MCS IK0193 Wagner Renewables Ltd.

Issue: 03

Product(s)

Model	Description	Reference No.
TRIC A On Roof Mounting System	Roof Installation Kit (Above Roof)	MCS IK0193/01

Which includes the following components:

Roof Anchors

TRIC P A2 Top Bracket TRIC P A2 HV Top Bracket TRIC TR Fix Roof Bracket TRIC P Alu HVN Top Bracket

TRIC P Low STV UK Bracket

TRIC P STV KF Top Bracket TRIC BE Roof Bracket for wood TRIC BE Roof Bracket for steel TRIC KA Roof Bracket for wood

TRIC KA Roof Bracket for fibre cement sheet roofs

TRIC LDC Mounting Rail TRIC HDC Mounting Rail

Clamp

TRIC Clip Module Fastener

Technical information for TRIC A On Roof Mounting System:

SYSTEM

Maximum design wind uplift: Value of partial safety factor:

2992.5Pa

1.1

COMPONENTS TRIC P A2 Bracket Roof substrate:

Minimum roof pitch: Maximum design wind uplift:

Value of partial safety factor:

Timber rafters (rafter size should be adequate to resist applied wind load and comply with current building regulations of the country in which installed)

513.2N 1.0

TRIC P A2 HV Bracket Roof substrate:

Minimum roof pitch: Maximum design wind uplift: Value of partial safety factor:

Timber rafters (rafter size should be adequate to resist applied wind load and comply with current building regulations of the country in which installed)

538.5N 1.0

TRIC TR Fix Trapezoidal Bracket Roof substrate:

Minimum roof pitch: Maximum design wind uplift: Value of partial safety factor:

Corrugated tin roof

2418.4N 1.25

ate and appendix is maintained and held in force through periodic review and verification.

Hobal Ltd.

John Holden

02 June 2017

20 June 2014

Business Group Manager

Date of Issue

Date of First Issue





This certificate and appendix remains the property of BRE Global Ltd and is issued subject to terms and conditions (for details visit www.greenbooklive.com/terms).

To check the validity of this certificate please visit www.greenbooklive,com/check or contact us.

BRE Global Ltd., Garston, Watford WD25 9XX.

T: +44 (0)333 321 8811 F: +44 (0)1923 664603 E: enquiries@breglobal.com MCS is the Certification Mark for Onsite Sustainable Energy Technologies





Appendix to Certificate No: MCS IK0193 Wagner Renewables Ltd.

Issue: 03

TRIC P Alu HVN Bracket

Roof substrate:

Minimum roof pitch: Maximum design wind uplift: Value of partial safety factor:

TRIC P Low Galv UK Bracket

Roof substrate:

Minimum roof pitch: Maximum design wind uplift: Value of partial safety factor:

TRIC P STV KF Bracket

Roof substrate:

Minimum roof pitch: Maximum design wind uplift: Value of partial safety factor:

TRIC KA Roof Bracket for wood/ TRIC KA Roof Bracket for fibre cement sheet roofs

Roof substrate:

Minimum roof pitch: Maximum design wind uplift: Value of partial safety factor:

TRIC BE Roof Bracket for wood

Roof substrate:

Minimum roof pitch: Maximum design wind uplift: Value of partial safety factor:

TRIC BE Roof Bracket for steel

Roof substrate: Minimum roof pitch: Maximum design wind uplift: Value of partial safety factor: Timber rafters (rafter size should be adequate to resist applied wind load and comply with current building regulations of the country in which installed)

10° 544.5 N 1.0

Timber rafters (rafter size should be adequate to resist applied wind load and comply with current building regulations of the country in which installed)

10° 941.9 N 1.0

Timber rafters (rafter size should be adequate to resist applied wind load and comply with current building regulations of the country in which installed)

10° 1355.9 N 1.0

Timber rafter (rafter size should be adequate to resist applied wind load and comply with current building regulations of the country in which installed)

10 7494 N 1.44

Timber rafter (rafter size should be adequate to resist applied wind load and comply with current building regulations of the country in which installed)

10° 4507 N 1.44

Steel purlin

1790 N 1.0

his vertificate and appendix is maintained and held in force through periodic review and verification.

John Holden Business Group Manager 02 June 2017 Date of Issue 20 June 2014

ue Date of First Issue

TO THE PARTY OF TH



BRE Global Ltd.

This certificate and appendix remains the property of BRE Global Ltd and is issued subject to terms and conditions (for details visit www.greenbooklive.com/terms).

To check the validity of this certificate please visit www.greenbooklive,com/check or contact us.

BRE Global Ltd., Garston, Watford WD25 9XX.

T: +44 (0)333 321 8811 F: +44 (0)1923 664603 E: enquiries@breglobal.com

MCS is the Certification Mark for Onsite Sustainable Energy Technologies

