Roof Bracket System TR fix



Two rail variants: short perforated rails or continuous rails

Roof bracket system TR fix for rapid mounting on shed roofs in combination with the patented module clamp TRIC clip. Enormously flexible applications with options of short rail segments or continuous mounting rails and sheet metal screws or rivets.



STANDOUTS

DETAILS

 Fast and simple installation 	Installation becomes childs play when using the pre-punched rail segments. Our patented TRIC clip module clamp additio- nally also assures safe and fast module mounting.
• Two rail variants	Depending on project requirements it is possible to either work with long, continuous rails or with short rail segments. This way the most economic solution is applied to each case.
• Two safe fastening variants	Depending on the trapezoidal sheets' properties and the struc- tural conditions, sheet metal screws or rivets are recommended. They establish a secure connection to the roof structure.
 Economic system pricing 	For each application case the most economic solution is chosen. Low material costs and short installation cycles combine into highly attractive systems pricing.

www.wagner-renewables.com







Set with short mounting rails and blind rivets



Set with sheet metal screws

Set with blind rivets



long mounting rail with Alu Fix-Profil



Roof Brackets TR fix for Trapezoidal Sheet Roofings, with Short Mounting Rails

- Fixed directly in the trapezoidal sheeting (screw or rivet)
- A set comprises: 2 TR fix rail sections, 21 × 66 mm, length 395 mm, with holes and coverd with neoprene underlays;
 - 8 x self tapping sheet metal screw or 8 x blind rivet with gasket;
- Structural rating is absolutely mandatory

Roof Brackets TRN for Trapezoidal Sheet Roofings, with Long Mounting Rails

- Fixed directly in the trapezoidal sheeting (screw or rivet)
- A set comprises: 22 x neoprene underlay sealant, 2 x self tapping sheet metal screw or 2 x blind rivet with gasket
- Only in connection with mounting rail
- Structural rating is absolutely mandatory

Module Fastener TRIC clip

- Module fasteners made from aluminum / stainless steel, completely pre-assembled
- Simple and safe installation with patented design
- Significantly time saving, in the right position with a flick of the hand
- Suitable for all TRIC mounting rails
- For all common modules with frame heights of 30-50 mm

Technical Data	Roof bracket system TR fix
Application	Trapezoidal Sheet Roofings
Rail variants	Short, punched rails (395 mm), continuous rails (6000 mm / 5200 mm)
Fastening variants	Self tapping sheet metal screws (for steel / aluminum sheeting from 0.5 mm), blind rivets (for Steel sheeting from 0.63 mm)
Module types	For all common framed modules
Naterial	Aluminum, stainless steel, EPDM
Product warranty	10 years

Wagner Renewables Ltd

Unit 1B, Keynor Farm, Sidlesham, Chichester, West Sussex, PO20 7LL Tel: 01243 641830 Email: info@wagner-renewables.com

01243 641830 info@wagner-renewables.com